



TAM-Europe d.o.o

www.tam-motors.eu
Production Base: Slovenia & China

VIVE Series **C7**

TECHNICAL SPECIFICATION

BASIC SPECIFICATION

Length/Width/Height(mm)	7300/2160/2840
Wheel Base(mm)	4100
Maximum Speed(km/h)	100
Passenger Capacity	29
Fuel Type	Diesel
Transmission	MT
Curb Weight(kg)	6500
GVW(kg)	7700
Body structure	Chassis frame
Number of Steps	2
Number of Doors	2
Front Axle(kg)	2700
Rear Axle(kg)	5000
Front Suspension	Leaf spring
Rear Suspension	Leaf spring
Front Track(mm)	1665
Rear Track(mm)	1525
Angle of Approach/Departure(°)	16/10
Gradeability(%)	≥20
Minimum Turning Radius(m)	7
A/C(kcal/h)	14000
Engine Model	YC4FA130-40/YC4FA130-50
Engine Type	4-cylinders/4-stroke/Liquid cooling/Direct injection
Displacement(cc)	2982
Emission Level	Euro 4/Euro 5
Maximum Power(kW/rpm)	95(130HP)/3200
Maximum Torque(N.m/rpm)	340/1600-2400
Transmission	6MT
Clutch	Diaphragm clutch
Retarder	N/A
Braking System	Front Disc/Rear drum
Steering System	Hydraulic power
Fuel Tank(L)	85
Tires	7.50R16
Passenger Door	●
Cabin door	-
Driver's Door	●
Emergency Door	-
Front Windshield	Laminated glass
Rear Windshield	Hardened glass
Floor	T12 Bamboo material
Floor Cover	Anti-fire, anti-slip, wooden grain wear-resistant floor leather
Driver's Seat	Air shock absorption with 3-point belt

